



HP	Volts	Phase	Hz	Harmonic	Kvar	Contactor	PQ Connect	Weight (lb)
25	600	3	60	5TH	8.3	With	With	130
30	480 & 600	3	60	5TH	10	With	With	140
40	480	3	60	5TH	15	With	With	180
40	600	3	60	5TH	9.9	With	With	180
50	480	3	60	5TH	15	With	With	180
50	600	3	60	5TH	14.9	With	With	180

Enclosure	Dimension Table			
	"A" Dim	"B" Dim	"C" Dim	"D" Dim
Type 1	26.5	23.0	2.0	1.2
Type 3R	28.5	22.1	3.9	2.1

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES.				TOLERANCES (EXCEPT AS NOTED) DECIMAL .XX ± .25 .XXX ± .10		TCI W132N10611 Grant Drive Germantown, WI 53022 © 2021 TCI, LLC An <i>allied motion</i> Company HarmonicShield, (PQ Connect) 30 to 50Hp / 480V, 25 to 50Hp / 600V		
A	As Designed	7/28/2021	DSW	ANGULAR	± 1°	DRN BY DSW	DATE 7/28/2021	109000DG
NO	REVISION	DATE	BY	SCALE	1:5	DRN BY DSW	DATE 7/28/2021	109000DG

- Notes:
- 1.) Refer to manual for wire size and torque.
 - 2.) Contactor (CNT) and terminal (TB) are optional.
 - 3.) PQconnect with Transformer are optional.
 - 4.) Refer to schematic # 30047, PQ Schematic (TBD)
 - 5.) Preferred wire entry area.
 - 6.) Wire entry is allowed through the bottom.
 - 7.) Enclosure is shown with a Type 3R top.
 - 8.) Use only hubs or fittings that comply with UL514B for Type 3R applications
 - 9.) Installation must meet all national and local codes.

Material(s) Shall be RoHS Compliant

A

A

C

B

D

D

C

B

A

4

3

2

1

4

3

2

1