



The 50A unit is rated for 39A when applied with a 480V/600V autotransformer

The 30A unit is rated for 23A when applied with a 480V/600V autotransformer

DRAWINGS:
 General Schematic: 32622
 Customer Connection: 32845
 Interface/Display module #28282-1
 Current Transformer #26461

Notes:
 Weight lbs (kg) 115 (52.2)
 *Maintain 3" side clearance, both sides, and 6" bottom clearance for cooling

Dimensions are in Inches

Heat loss Watts (Btu/hr):
 30A: 855 Watts (2917 Btu/hr)
 50A: 1425 Watts (4862 Btu/hr)

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES.

NO	REVISION	DATE	BY
B	AS UPDATED	11/21/23	MJS
A	as designed	1/17/23	MJS

TOLERANCES (EXCEPT AS NOTED)	
DECIMAL	
.XX	± .03
.XXX	± .010
FRACTIONAL	
± 1/32	
ANGULAR	
± 1°	

 TCI An Allied Motion Company		W132N10611 Grant Drive Germantown, WI 53022 © 2024 TCI, LLC	
		Outline / Installation, ALC30/50A, Type 1	
DRN. BY MJS	DATE: 1/17/23	109324	
SCALE: yes	APRVD:	SIZE B	SHT.1 OF 1