



Notes:
 Weight lbs (kg) 98 (44.5)
 Dimensions are in inches
 Heat loss Watts (Btu/hr):
 30A: 855 Watts (2917 Btu/hr)
 50A: 1425 Watts (4862 Btu/hr)

Drawings:
 General Schematic: 32622
 Customer Connection: 32845
 Interface/Display module #28282-1
 Current Transformer #26461

The 50A unit is rated for 39A when applied with a 480V/600V autotransformer

The 30A unit is rated for 23A when applied with a 480V/600V autotransformer

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES.

A	AS DESIGNED	1/17/24	MJS	
NO	REVISION	DATE	BY	

TOLERANCES (EXCEPT AS NOTED)
DECIMAL
.XX ± .03
.XXX ± .010
FRACTIONAL
± 1/32
ANGULAR
± 1°

		W132N10611 Grant Drive Germantown, WI 53022 © 2024 TCI, LLC
OUTLINE/INSTALLATION, ALC30/50A, OPEN CHASSIS		
DRN. BY MJS	DATE: 1/17/24	109559
SCALE: yes	APRVD:	SIZE B
		SHT.1 OF 1