


Drawings:
General Schematic: 33118
Customer Connection: #25027-3
Cooling Drawing: 33205
Interface/ Display Module: #28282-1 & #28283-1
Current Transformer: #26461

Notes:
Weight lbs (Kg): 344 lbs (156 kg)
Front view is shown with cover removed over the converter.
Total heat loss:
200A: 5,470 W, 18,664 Btu/h
250A: 6,750 W, 23,032 Btu/h
Interface/ Display Module is supplied loose for remote mounting, cables included.
Additional depth may be required for breaker door handle mechanism.

The 200A unit is rated for 150A when applied with a 480V/ 600V autotransformer

The 250A unit is rated for 185A when applied with a 480V/ 600V autotransformer

TOLERANCES (EXCEPT AS NOTED)	THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIENT INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIENT INC. AND ITS SUBSIDIARIES.						DRN. BY		W132N10611 Grant Drive Germantown, WI 53022 © 2024 Allient Inc.	
DECIMAL							JSG			
.XX ± .03 .XXX ± .010							DATE: 10/30/24			
FRACTIONAL ± 1/32							Outline, Installation, 200/250A 3 Level Active Filter Chassis			
ANGULAR ± 1°		A		As designed	3/19/25	JSG				
	NO	ECO	REVISION	DATE	BY	SCALE: 1:8.5	DRN. NO. 109667	SIZE B	SHT.1 OF 1	