



Drawings:
General Schematic: 33118
Customer Connection: 25027-3
Interface /Display Module: 28283-1
Current Transformer: 26461

Notes:
1) Maintain 6" side clearance
both sides for cooling.
2) Maintain 6" floor clearance
for cooling.

Weight lbs (Kg): 424 Lbs (192.3 Kg)
Total Heat Loss:
200A: 5,540 W, 18,903 Btu/h
250A: 6,820 W, 23,271 Btu/h
The 200A unit is rated for 150A when applied
with a 480V / 600V autotransformer.
The 250A unit is rated for 185A when applied
with a 480V / 600V autotransformer.

TOLERANCES (EXCEPT AS NOTED)				HOLE TOLERANCE $\pm .005$			
DECIMAL				DRN. BY			
.XX $\pm .03$				JSG			
.XXX $\pm .010$				DATE:			
FRACTIONAL				10/30/24			
$\pm 1/32$				Outline, Installation, 200A/250A 3 Level, Active Filter Type 1			
ANGULAR				SCALE:			
$\pm 1^\circ$				1:15			
THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIENT INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIENT INC. AND ITS SUBSIDIARIES.				DRN. NO.			
				109668			
				SIZE			
				B			
				SHT.1 OF 1			