


SECTION A-A
SCALE 1 / 14

Drawings:
General schematic: 33207
Customer Connection: 25027-3
Interface / Display Module: 28283-1
Current transformer: 26461

The 200A unit is rated for 150A when applied with a 480V / 600V autotransformer.

The 250A unit is rated for 185A when applied with a 480V / 600V autotransformer.

Notes:
Weight lbs (Kg): 704 lbs (319 kg)
Total heat loss:
200A: 5,870 W, 20,029 BTU/Hr
250A: 6,820 W, 24,397 BTU/Hr

TOLERANCES (EXCEPT AS NOTED)		THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIENT INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIENT INC. AND ITS SUBSIDIARIES.				DRN. BY				W132N10611 Grant Drive Germantown, WI 53022 © 2024 Allient Inc.							
DECIMAL						JSG											
.XX ± .03 .XXX ± .010						DATE:		10/31/24									
FRACTIONAL ± 1/32										Outline Installation, N3R Gen II, Active Filter, 200/250A							
ANGULAR ± 1°		A		As Designed		3/26/25		JSG									
		NO		ECO		REVISION		DATE		BY		SCALE:		DRN. NO.		SIZE	
												1:12		109669		B	
																SHT.1 OF 1	

HOLE TOLERANCE ± .005

Outline Installation, N3R
Gen II, Active Filter, 200/250A