


The 400A unit is rated for 300A when applied with a 480V / 600V autotransformer.

The 500A unit is rated for 370A when applied with a 480V / 600V autotransformer.

Drawings:  
General Schematic : 33118-1  
Customer Connection: 25027-3  
Interface / Display Module: 28282-1 & 28283-1  
Current transformer: 26461

Notes:  
Weight lbs (Kg): 592 lbs (269 kg)  
Front view is shown with cover removed over the converter.  
Total heat loss:  
400A: 10,930 W, 37,295 Btu/h  
500A: 13,490 W, 46,030 Btu/h  
Interface/ Display module is supplied loose for remote mounting, cables included.  
Additional depth may be required for breaker door handle mechanism.

HOLE TOLERANCE ± .005

TOLERANCES (EXCEPT AS NOTED)	THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIENT INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIENT INC. AND ITS SUBSIDIARIES.					DRN. BY		W132N10611 Grant Drive Germantown, WI 53022 © 2024 Allient Inc.		
DECIMAL						JSG				DATE:
.XX ± .03							10/31/24	Installation Outline, 3 Level 400A / 500A Active Filter, Chassis		
.XXX ± .010										
FRACTIONAL ± 1/32										
ANGULAR ± 1°		A		As designed	3/26/25	JSG	SCALE:	DRN. NO.	SIZE	SHT.1 OF 1
		NO	ECO	REVISION	DATE	BY	1:12	109670	B	