


- Notes:
1. Mounting hole diameter is .64"
  2. The "A" mounting holes are mandatory. The "B" mounting holes are optional.
  3. To insure proper cooling maintain 6" clearance on sides and front.

Weight: 842 lbs (382 kg)  
Total Heat Loss:  
400A: 11,080 W, 37,807 Btu/h  
500A: 13,640 W, 46,542 Btu/h  
Drawings:  
General schematic : 33118-1  
Customer connection: 25027-3  
Interface/Display module: 28283-1  
Customer transformer: 26461

WARNING:  
Filter must be securely anchored to the floor to avoid a tripping hazard!

The 400A unit is rated for 300A when applied with a 480V/600V autotransformer.  
The 500A unit is rated for 370A when applied with a 480V/600V autotransformer.

TOLERANCES (EXCEPT AS NOTED)		THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIENT INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIENT INC. AND ITS SUBSIDIARIES.								DRN. BY				W132N10611 Grant Drive Germantown, WI 53022 © 2024 Allient Inc.			
DECIMAL										JSG							
.XX ± .03										DATE:		11/06/24					
.XXX ± .010																	
FRACTIONAL ± 1/32														Outline, Installation Gen II Type 1 400A/500A Active Filter, Floor mount			
ANGULAR ± 1°		A		As Designed		3/26/25		JSG									
		NO		ECO		REVISION		DATE		BY		SCALE: 1:18		DRN. NO. 109671		SIZE B SHT.1 OF 1	