


- NOTES:
- 1) Refer to interface/display module: 28282-1 & 28283-1.
 - 2) Total heat dissipation:
 - 400A: 11,510 watts, 39,274 Btu/ hr.
 - 500A: 14,070 watts, 48,009 Btu/hr.
 - 3) Weight in Lbs (kg): 1200 Lbs (544 kg).
 - 4) General schematic drawing: 33118-1.
 - 5) Current transformer drawing: 26461.
 - 6) Customer connection diagram: 25027-3.
 - 7) The 400A unit is rated for 300A when applied with a 480V/600V autotransformer.
 - 8) The 500A unit is rated for 370A when applied with a 480V/600V autotransformer.

DIMENSIONS IN INCHES (EXCEPT AS NOTED)	THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIENT INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIENT INC. AND ITS SUBSIDIARIES.						DRN. BY		W132N10611 Grant Drive Germantown, WI 53022 © 2025 Allient Inc.				
							JSG						
							DATE:						
		TOLERANCES (EXCEPT AS NOTED)						1/28/25	Outline, Installation Gen II Type 3R 400A/500A Active Filter, Floor mount				
		DECIMAL											
.XX ± .03							SCALE:			DRN. NO.	SIZE	SHT.1 OF 1	
.XXX ± .010													1:20
FRACTIONAL													
± 1/32		A		As Designed		3/28/25	JSG						
ANGULAR		NO	ECO	REVISION		DATE	BY						
± 1°													