


TCI Part Number	Rated Amps (A)	Rated Voltage (V)	Hz	---uH ±5%	Approx Weight (LBS)	Attached Lug Kit
KTRMG362AX6	362	480	60	132	295	SLK13

Wire Range	Tightening Torque
350MCM - 2 AWG	375 Lbs-In (42.4 N-m)
2 AWG - 6 AWG	275 Lbs-In (31.1 N-m)

- Notes:
1. UL file number: cULus Listed File E116124.
  2. KTRMG Reactors Comply With The Thermal and Altitude Standards Set Forth by NEMA ST20-1992.
  3. Material(s) Shall be RoHS Compliant
  4. Customer Is Responsible For Installation To Meet All National And Local Electrical Codes.

DIMENSIONS IN INCHES (EXCEPT AS NOTED)  TOLERANCES (EXCEPT AS NOTED) DECIMAL .XX ± .25 .XXX ± .10 FRACTIONAL ± 1/16 ANGULAR ± 1°	THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIENT INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIENT INC. AND ITS SUBSIDIARIES.						DRN. BY	JRN		W132N10611 Grant Drive Germantown, WI 53022 © 2025 Allient Inc.	
								DATE			06/03/25
		KTRMG, 362A, 480V Reactor Drawing, With Lugs									
		SCALE: 1/2									
		A	As Designed		06/03/25	JRN		DRN. NO.	109800DG	SIZE C	SHT.1 OF 1
		NO	ECO	REVISION	DATE	BY					
		2		1							