


NOTE:
REFER TO GENERAL SCHEMATIC: 33353
REFER TO CUSTOMER CONNECTION DIAGRAM, 30/50A: 25027-3
INTERFACE DISPLAY MODULE DRAWING: 28282-1
CURRENT TRANSFORMER DRAWING: 26461

WEIGHT: 395 Lbs [180 Kg]

TOTAL HEAT LOSS 30A: 1070W [3650 BTU/Hr]
50A: 1640W [5595 BTU/Hr]

FINISH: ANSI-61 GRAY POWDER COAT INSIDE AND OUT.
SUBPANEL IS POWDER COATED WHITE.

HOLE TOLERANCE ± .005

TOLERANCES (EXCEPT AS NOTED)	THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIENT INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIENT INC. AND ITS SUBSIDIARIES.						DRN. BY RJH		W132N10611 Grant Drive Germantown, WI 53022 © 2025 Allient Inc.	
DECIMAL							DATE: 09/05/25			
.XX ± .25 .XXX ± .010										
FRACTIONAL ± 1/16							Outline, Installation, Active Filter, 30-50A, NEMA 12			
ANGULAR ± 1°		A	As Designed	09/05/25	RJH					
		NO	ECO	REVISION	DATE	BY	SCALE: To Fit	DRN. NO. 109858	SIZE B	SHT.1 OF 1