







| V1K Part Number | Max Voltage | Amps | Phase | Weight (LBS) |
|-----------------|-------------|------|-------|--------------|
| V1K27A03EX | 600 | 27 | 3 | 30 |
| V1K27A03EXT | 600 | 27 | 3 | 30 |

T - Thermal Switch Option



(Customer Connections) Markings On Terminal Block For Reference Only.



See V1K Installation Guide For Terminal Wire Size And Torque Information.

Note: Maintain Clearance of 3 Inches On All Sides To Other Equipment.

Note: Use Only Hubs Or Fittings That Comply With UL514B For Type 3R Enclosures.

Customer Is Responsible For Installation To Meet All National And Local Electrical Codes.

Material(s) Shall be RoHS Compliant

| | | | | | | |
|---|--|---|-------------------|------------|-------------------|---|
| DIMENSIONS IN INCHES (EXCEPT AS NOTED) TOLERANCES (EXCEPT AS NOTED) DECIMAL .XX ± .25 .XXX ± .10 FRACTIONAL ± 1/32 ANGULAR ± 1° | | THE INFORMATION AND DESIGN CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIANT INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIANT INC. AND ITS SUBSIDIARIES. | | DES BY DSW | DATE 2/13/26 | W132N10611 Grant Drive Germantown, WI 53022 © 2026 Alliant Inc. |
| NO ECO | | 7396 | KDRB2Q to KDRBA2Q | 2/13/26 | DSW | V1K, Enclosed Type 3R, Heavy Duty 27 Amps |
| REVISION | | DATE | BY | SCALE 1/2 | DES. NO. 109881-1 | SIZE C |
| | | | | | | SHT. 1 OF 1 |