



CUSTOMER CONNECTIONS
 WIRE RANGE- ONE 600MCM-4
 TWO 250MCM-1/0
 TIGHTENING TORQUE 500 IN-LB.

GROUND LUG:
 WIRE RANGE- ONE 600MCM-4
 TWO 250MCM-1/0
 TIGHTENING TORQUE 500 IN-LB.

UNIT SPECIFICATIONS:					
KVAR HARMONIC	VOLT	HZ	PHASE	HP	
30	5TH	240	60	3	100
ENCLOSURE	NEMA 1				
APPROX.WT. LBS.	285				

SYMBOL	TCI PART NUMBER
LR	KDRJ22T
TR	KTR30B65HG
CAP1, 2, 3	10 KVAR KCAP10B6B
Fu1, 2, 3	11305

FOR SCHEMATIC SEE 25179
 CUSTOMER IS RESPONSIBLE FOR INSTALLATION
 TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

TCI, LLC CLAIMS PROPRIETARY RIGHTS IN THE MATERIAL HEREIN DISCLOSED. IT IS SUPPLIED WITHOUT PREJUDICE TO ANY PATENT RIGHTS OF TCI AND MAY NOT BE REPRODUCED OR USED TO MANUFACTURE ANYTHING SHOWN THEREIN WITHOUT WRITTEN PERMISSION FROM TCI.				TOLERANCES (EXCEPT AS NOTED): DECIMAL	W132 N10611 Grant Drive Germantown, WI 53022
				.XX ±.03	
					.XXX ±.01
	B	COLOR WAS BLACK	1/25/12	RJC	FRACTIONAL ± 1/32
	A	2516, CAP WAS 17813	9/30/07	RJC	ANGULAR ± 1/2°
NO	REVISION	DATE	BY	SCALE TO FIT	DRN. BY DSW DATE 4/22/05 DWG. NO. 102523DG SIZE C SHT.1 OF 1