



CUSTOMER CONNECTIONS  
 WIRE RANGE- 250MCM-6  
 TIGHTENING TORQUE 275 IN-LB.

GROUND LUG:  
 WIRE RANGE- 250MCM-6  
 TIGHTENING TORQUE 275 IN-LB.

UNIT SPECIFICATIONS:					
KVAR HARMONIC	VOLT	HZ	PHASE	HP	
40	5TH	600	60	3	125
ENCLOSURE		NEMA 1			
APPROX.WT. LBS.		308			

SYMBOL	TCI PART NUMBER
LR	KDRL41T
TR	KTR40C65HG
CAP1, CAP2.	KCAP20C6B
Fu1, 2, 3	19061

FOR SCHEMATIC SEE 25115

CUSTOMER IS RESPONSIBLE FOR INSTALLATION  
 TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

TCI, LLC CLAIMS PROPRIETARY RIGHTS IN THE MATERIAL HEREIN DISCLOSED. IT IS SUPPLIED WITHOUT PREJUDICE TO ANY PATENT RIGHTS OF TCI AND MAY NOT BE REPRODUCED OR USED TO MANUFACTURE ANYTHING SHOWN THEREIN WITHOUT WRITTEN PERMISSION FROM TCI.				TOLERANCES (EXCEPT AS NOTED): DECIMAL	<b>TCI</b> ® W132 N10611 Grant Drive Germantown, WI 53022	
				.XX ±.03 .XXX±.01		
					FRACTIONAL ± 1/32	HG125CW01ST, HG7 STANDARD 125 HP, 600/3/60, TYPE 1
					ANGULAR ± 1/2°	
	NO	REVISION	DATE	BY	DRN. BY DSW DATE 3/17/05 DWG. NO. 102491DG SCALE TO FIT SIZE C SHT.1 OF 1	