


GROUND LUG:
 WIRE RANGE—ONE 600MCM-4
 TWO 250MCM-1/0
 TIGHTENING TORQUE 500 IN-LB.

UNIT SPECIFICATIONS:					
KVAR	HARMONIC	VOLT	HZ	PHASE	HP
60	5TH	600	60	3	200
OPEN PANEL		WHITE			
FEATURES		WITH CONTACTOR			
APPROX.WT. LBS.		360			



CUSTOMER CONNECTIONS:
 WIRE RANGE—ONE 600MCM-4
 TWO 250MCM-1/0
 TIGHTENING TORQUE 500 IN-LB.

SYMBOL	HG200CW00STC
LR	X
TR	X
CAP1,2,3	X
Fu1,2,3	X
Fu4,6	X
CNT	X
XFMR	X

FOR SCHEMATIC SEE DWG# 26879

CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF FILTER COMPONENTS. CAPACITORS MAXIMUM AMBIENT 50°C

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

				TOLERANCES (EXCEPT AS NOTED)	TCI W132 N10611 GRANT DRIVE GERMANTOWN, WI. 53022
				DECIMAL	
				.XX ± .03	HG200CW00STC, HG7 W/CNT 200 HP, 600/3/60, OPEN
				.XXX ± .01	
				FRACTIONAL ± 1/32	
A	3267 CONTACTOR CHANGE	6/22/15	BWM	ANGULAR ± 1/2°	DRN. BY DSW DATE 4/2/09 DWG. NO. 103577DG
NO	REVISION	DATE	BY		SCALE TO FIT APRVD. B SHT.1 OF1