


NOTE: USE ONLY HUBS OR FITTINGS THAT COMPLY
WITH UL514B FOR TYPE 3R ENCLOSURES.

HP
450

RAINHOOD
4 PLACES.

FU1
FBLK FU2
FU3

REMOVEABLE
CENTER CHANNEL



GROUND LUG:
WIRE RANGE-TWO 600MCM-2
TIGHTENING TORQUE 500 IN.-LB.



TCI, LLC CLAIMS PROPRIETARY RIGHTS IN THE MATERIAL HEREIN DISCLOSED. IT IS SUPPLIED WITHOUT PREJUDICE TO ANY PATENT RIGHTS OF TCI AND MAY NOT BE REPRODUCED OR USED TO MANUFACTURE ANYTHING SHOWN THEREIN WITHOUT WRITTEN PERMISSION FROM TCI.						TOLERANCES (EXCEPT AS NOTED)	 w132 N10611 Grant Drive Germantown, WI 53022
						DECIMAL	
						.XX ± .12	
						.XXX ± .06	
						FRACTIONAL	
						± 1/32	
A WAS KTR150C65HG							HG450CW03ST, 450HP
15 KVAR CAP WAS 10			9/13/11	RJC			600/3/60 UL TYPE 3R
NO REVISION			DATE	BY	ANGULAR	DRAWN BY DSW	DATE 2/26/09 DWG NO. 103648DG
					SCALE 1" = 1"	SIZE 11	SHT 1 OF 1