

UNIT SPECIFICATIONS:								
KVAR HARME	INIC V	'DLT	HΖ	PHASE	HP			
15 5TI	Н а	240	60	3	50			
ENCLOSURE	UL	TYP	E 3R					
COLOR	WH	HITE						
FEATURES	CON	CONTACTOR						
APPROX.WT. L	BS. 21	5						

	HG50BW03STC		
	COMPONENTS		
Ī	LINE REACTOR	Χ	
L	LR		
	TRAP REACTOR	χ	
	TR		
	CAPACIT□R	Х	
	CAP		
	TRAP FUSING	χ	
	FU1,2,3	, · ·	
	XFMR	Χ	
	XFMR	χ	
	FU4,6		
Ī	XFMR	χ	
	FU5	_ ^	
Ī	CNT	Χ	
L	9-11		

CUSTOMER CONNECTIONS:

WIRE RANGE-250MCM-6

TIGHTENING TORQUE 275 IN-LB.

GROUND LUG:

WIRE RANGE-250MCM-6

TIGHTENING TORQUE 275 IN-LB.

				TOLERANCES	4
_				(EXCEPT AS NOTED)	1
				DECIMAL	
				.XX ± .12	
				.XXX± .03	Ηľ
В	3033 UPDATE LAYOUT	2/24/14	DSW	FRACTIONAL ± 1/32	2.
Α	2641 ADD EYEBOLTS	10/21/09	DSM	ANGULAR	DRN. BY
NΠ	REVISION	DATE	BY	± 1/2°	SCALE

7878 N. 86th STREET MILWAUKEE, WI 53224

HG50BW03STC, 50HP 240/3/60 UL TYPE 3R

DSW | DATE 12/22/08 | DWG. NO. 103716DG | C SHT. 1 DF1