



SEE 25179 FOR SCHEMATIC

UNIT SPECIFICATIONS:					
KVAR HARMONIC	VOLT	HZ	PHASE	HP	
20	5TH	240	60	3	60
ENCLOSURE		WHITE OPEN PANEL			
APPROX.WT. LBS.		120			

SYMBOL	TCI PART NUMBER
LR	KDRG22T
TR	KTR20B65HG
CAP1, 2, 10 KVAR	KCAP10B6B
Fu1, 2, 3	15740

CUSTOMER CONNECTIONS:
 WIRE RANGE-250MCM-6
 TIGHTENING TORQUE 275 IN-LB.

GROUND LUG:
 WIRE RANGE-250MCM-6
 TIGHTENING TORQUE 275 IN-LB.

CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF FILTER COMPONENTS.
 CAPACITORS MAXIMUM AMBIENT 50°C

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

				TOLERANCES (EXCEPT AS NOTED)	7878 N. 86th STREET MILWAUKEE, WI 53224
				DECIMAL	
				.XX ± .03 .XXX ± .01	
				FRACTIONAL ± 1/32	
△	2516, CAP WAS 17813	9/30/07	RJC	ANGULAR ± 1/2°	DRN. BY DSW
NO	REVISION	DATE	BY		DATE 04/14/05
					APRVD.
					DWG. NO. 102520DG
					SCALE TO FIT
					B
					SHT. 1 OF 1