

| CATALOG NO | VOLTAGE | NEC MOTOR HP | NEC MOTOR CURRENT | WATTS LOSS | APPROX. WEIGHT-LBS | TORQUE (LB-IN) |
|------------|---------|--------------|-------------------|------------|--------------------|----------------|
| KDRA28LDR | 208/240 | 3.0 | 10.6 | 29 | 4 | 10 |

NEC MOTOR CURRENTS SHOWN IN THE 208/240 VOLT CHART ARE BASED ON HORSE POWERS AT 208 VOLT. 575/600 VOLT CHART USE THE 575 VOLT CURRENT RATING.

KDR DRIVE REACTORS COMPLY WITH THE THERMAL AND ALTITUDE STANDARDS SET FORTH BY NEMA ST20-1992..


TCI Performance and Protection for Drives.

TRANS-COIL, INC
MILWAUKEE, WI
WWW.transcoil.com
800-824-8282

KLR Series Line Reactor
CATALOG#
3PH, 60Hz, 600V Max, --- Amps
40C Amb Max, 115C Rise

UL® US®
CE


A1 A2 B1 B2 C1 C2




NOTE: A1, A2, B1, B2, C1, C2, ON TERMINAL BLOCK FOR REFERENCE ONLY.

BLOCK WIRE RANGE #12-#18 AWG FOR REACTOR AND TIGHTENING TORQUE. 10 LB-IN

TCI'S DIN RAIL MOUNTED REACTORS FIT STANDARD 35mm DIN RAIL. TCI'S MINIMUM RECOMMENDATION IS TO USE: HIGH PROFILE STANDARD 35mm STEEL RAIL OR HEAVY DUTY STANDARD 35mm STEEL RAIL.




STANDARD STEEL HIGH PROFILE DIN RAIL.



HEAVY DUTY STEEL DIN RAIL.

TCI RECOMMENDS TAKING PRECAUTIONS WHEN SHIPPING MOUNTED REACTORS.

NOTE: CUSTOMER CAN CHANGE MOUNTED REACTOR, FROM VERTICAL TO HORIZONTAL ON DIN BRACKET.



| NO | REVISION | DATE | BY | TOLERANCES (EXCEPT AS NOTED) DECIMAL | DRN BY | DATE | DWG NO |
|----|----------|------|----|--------------------------------------|--------|------------|-------------|
| | | | | .XX ± .03 .XXX ± .01 | DSW | 11/29/2011 | KDRA28LDRDG |
| | | | | FRACTIONAL ± 1/32 | | | C |
| | | | | ANGULAR ± 1/2° | | | SHT.1 OF1 |

TCI 7878 N. 86th STREET MILWAUKEE, WI 53224

KDR 208/240 DIN RAIL FRAME A