



KEYSLOTS FOR
1/4-20 SCREWS
2 PLACES

COVER IN
PLACE

.328 DIA.
2 HOLES

.44 DIA.
4 MTG. HOLES

LOCATION FOR
CUSTOMERS
CONDUIT FITTING
(BOTH SIDES)

CUSTOMER IS RESPONSIBLE FOR INSTALLATION
TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

690V	NEC MOTOR HP	CATALOG NO	__AMPS(A)	APPROX WT-LBS	WATTS LOSS	TERMINAL RING HOLE SIZE
3% Z	125	KLR130DCB4V	130	82	242	.28 DIA HOLE

TOLERANCES EXCEPT AS NOTED				TDCI 7878 N. 86th STREET MILWAUKEE, WI 53224	
NORMAL				KLR SERIES 3 PH REACTOR 690V (FRAME I) ENCLOSED	
.XX ± .03				DRAWN BY DSW DATE 03/30/07 DWG. NO. KLR130DCB4VDG	
.XXX ± .010				SCALE TO FIT	
FRACTIONAL ± 1/16				SHT. 1 OF 1	
ANGULAR ± 1/2°					
NO	REVISION	DATE	BY		