



KEYSLOTS FOR  
1/4-20 SCREWS  
2 PLACES

COVER IN  
PLACE

.328 DIA.  
2 HOLES

.44 DIA.  
4 MTG. HOLES

LOCATION FOR  
CUSTOMERS  
CONDUIT FITTING  
(BOTH SIDES)

CUSTOMER IS RESPONSIBLE FOR INSTALLATION  
TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

690V	NEC MOTOR HP	CATALOG NO	__AMPS(A)	APPROX WT-LBS	WATTS LOSS	TERMINAL RING HOLE SIZE
3% Z	150	KLR160DCB4V	160	82	261	.34 DIA HOLE

TOLERANCES EXCEPT AS NOTED				TDCI 7878 N. 86th STREET MILWAUKEE, WI 53224	
GENERAL				KLR SERIES 3 PH REACTOR 690V (FRAME I) ENCLOSED	
.XX ± .03				DRAWN BY DSW DATE 03/30/07 DWG. NO. KLR160DCB4VDG	
.XXX ± .010				SCALE TO FIT	
FRACTIONAL ± 1/16				SHT. 1 OF 1	
ANGULAR ± 1/2°					
NO	REVISION	DATE	BY		