



Technical data and measuring conditions.

Rated Voltage V_R	760/440 V AC, 50/60Hz.
Rated Current I_R	Referred to 40 °C ambient temperature 3270 V DC, 2 s (line/line) 2890 V DC, 2 s (line/case)
Test Voltage V_{test}	3270 V DC, 2 s (line/line) 2890 V DC, 2 s (line/case)
Overload Capability (thermal)	1.5 · I_R for 3 min per hour or 2.5 · I_R for 30 s per hour
Leakage Current I_{leak}	At 760 V AC, 50 Hz.
Climatic Category (IEC 60068-1)	25/100/21 (-25 °C/+100 °C/21 days damp heat test)
Approval Standards	EN 133200, UL 1283, CSA C22.2 No. 8
Approval Markings	UR, cUR

V_R	I_R	I_{leak}	$R_{typ.}$	Approx. Weight
AC V	A	mA	μ ohm	kg. / lbs.
760/440	150	< 28	140	13 / 28.6

			TOLERANCES (EXCEPT AS NOTED)	W132 N10611 Grant Drive Germentown, WI 53022
			DECIMAL	
			.XX ± .02	KRF FILTER KRF0180VCB, 600-690V, 180A
			.XXX ± .01	
ECO 3959 ADDED	4/24/17	JRN	FRACTIONAL ± 1/32	DRN BY DSW DATE 1/06/2010 DWG. NO. C KRF0180VCB
APPROVAL MARKINGS			ANGULAR ± 1/2°	SCALE TO FIT APRVD.
NO	REVISION	DATE	BY	SHT.1 OF1