


Technical data and measuring conditions.

Rated Voltage VR	760/440 V AC, 50/60Hz.			
Rated Current Ir	Referred to 40 °C ambient temperature			
Test Voltage Vtest	3270 V DC, 2 s (line/line)			
	2890 V DC, 2 s (line/case)			
Overload Capability (thermal)	1.5 · Ir for 3 min per hour or			
	2.5 · Ir for 30 s per hour			
Leakage Current I _{leak}	At 760 V AC, 50 Hz.			
Climatic Category (IEC 60068-1)	25/100/21 (-25 °C/+100 °C/21 days damp heat test)			
Approval Standards	EN 133200, UL 1283, CSA C22.2 No. 8			
Approval Markings	UR, CUR			

V _R	I _R	I _{leak}	R _{typ.}	Approx. Weight
AC	A	mA	μ ohm	kg. / lbs.
V				
760/440	1000	< 28	33	42 / 92.6

TOLERANCES		DECIMAL		FRACTIONAL		ANGULAR	
EXCEPT AS NOTED		.XX ± .02		.XXX ± .01		± 1/32	
ECDD 5456	UPDATED WEIGHT	11/24/20	JRN				
ECDD 3959	ADDED	4/24/17	JRN				
APPROVAL MARKINGS		DATE	BY				
ND	REVISION						



KRF FILTER
 KRF1000V/CB, 600-690V, 1000A
 DRN. BY DSV DATE 1/06/2010 DWG. NO. KRF1000V/CB
 SCALE 10 FIT APPRVD. SH. 1 OF 1