



### Technical data and measuring conditions.

Rated Voltage $V_R$	760/440 V AC, 50/60Hz.
Rated Current $I_R$	Referred to 40 °C ambient temperature 3270 V DC, 2 s (line/line) 2890 V DC, 2 s (line/case)
Test Voltage $V_{test}$	1.5 · $I_R$ for 3 min per hour or 2.5 · $I_R$ for 30 s per hour
Overload Capability (thermal)	At 760 V AC, 50 Hz.
Leakage Current $I_{leak}$	25/100/21 (-25 °C/+100 °C/21 days damp heat test)
Climatic Category (IEC 60068-1)	EN 133200, UL 1283, CSA C22.2 No. 8
Approval Standards	UR, cUR
Approval Markings	

$V_R$	$I_R$	$I_{leak}$	$R_{typ.}$	Approx. Weight
AC V	A	mA	$\mu$ ohm	kg. / lbs.
760/440	1600	< 28	22	34 / 74.8

			TOLERANCES (EXCEPT AS NOTED):		W132 N10611 Grant Drive Germantown, WI 53022
			DECIMAL		
			.XX ±.02		KRF FILTER KRF1600VCB, 600-690V,1600A
			.XXX±.01		
ECO 3959 ADDED		4/24/17	JRN	FRACTIONAL	DRN BY DSW DATE 1/06/2010 DWG. NO. CKRF1600VCB
APPROVAL MARKINGS				± 1/32	SCALE TO FIT
NO	REVISION	DATE	BY	ANGULAR	APPRD.
				± 1/2°	SHT.1 OF1